



**Salient Features**

- Screwed Male End to IS 554 / BS 21 / ISO 7.
- Spring Operated, Push Type, Self-Closing.
- Medium Pattern.
- Polished Body.

Can also be supplied with Chrome Plating, at a nominal extra price.

**Suitable For**

- Steam
- Water
- Oil
- Air
- Gases


Test Pressure (Hydraulic) Shell : 20 kg/cm<sup>2</sup>g (285 psig) Seat : 13.50 kg/cm<sup>2</sup>g (192 psig)

**Materials of Construction**

Name of Part	Material	Specification
Outlet Body	Bronze	IS 318 Gr. LTB 2
Inlet Body	Bronze	IS 318 Gr. LTB 2
Disc Holder & Stem	Bronze	IS 318 Gr. LTB 2
Disc	Nitrile Rubber	IS 5192-1
Packing Ring	Nitrile Rubber	IS 5192-1
Joint Washer	Leather	-
Spring	Stainless Steel	AISI 304

**Sizes / Dimensions**

Inches	mm	A
1/2	15	112



Zoloto Industries  
Zoloto House, 11th Milestone, Lambra, Nakodar Road,  
Jalandhar - 144 026  
Punjab, India

Phones : +91 181 4676666 (100 Lines)  
Facsimile : +91 181 2792500 & 2251600  
Email : zoloto@vsnl.com & sales@zolotovalves.com  
Web : <http://www.zolotovalves.com>