



**Salient Features**

- Wafer Type Design, thus taking lesser space than the conventional Check Valve.
- Being light in weight, is more rigid than the standard Swing Type Check Valve, which otherwise needs expensive foundation and special supports.
- Being cylindrical in body, stresses are uniformly distributed.
- Can be installed in Vertical or Horizontal pipe lines.
- Much longer seat life because of Bronze / S.S to Rubber contact.
- Low wear and tear of seat surfaces.
- End connections are designed to suit flanges drilled to ANSI B Class-125 / Class-150.

**Suitable For**

Steam
Water
Oil
Air
Gases


Test Pressure (Hydraulic) Shell : 24.50 kg/cm<sup>2</sup>g (350 psig) Seat : 14 kg/cm<sup>2</sup>g (200 psig)  
Working Temperature : -18°C to 80°C

**Materials of Construction**

Name of Part	Material	Specification
Body	Cast Iron	IS 210 Gr. FG 200
Flap	Bronze / S.S	IS 318 Gr. LTB 2 / AISI 304
Pin, Washer & Spring	Stainless Steel	AISI 316 / 304
Body Ring	EPDM / Nitrile Rubber	IS 5192-1
Retainer Hook	Carbon Steel	IS 1871

**Sizes / Dimensions**

Inches	mm	A	B	C
1 1/2	40	50	92	40
2	50	54	101	50
2 1/2	65	54	120	65
3	80	57	133	80
4	100	64	171	100
5	125	70	193	125
6	150	76	218	150
8	200	95	276	200
10	250	108	336	250
12	300	143	406	300
14	350	184	451	350
16	400	191	514	400



Zoloto Industries  
Zoloto House, 11th Milestone, Lambra, Nakodar Road,  
Jalandhar - 144 026  
Punjab, India

Phones : +91 181 4676666 (100 Lines)  
Facsimile : +91 181 2792500 & 2251600  
Email : zoloto@vsnl.com & sales@zolotovalves.com  
Web : http://www.zolotovalves.com