



Salient Features

- Flanged Ends to BS 10 Table 'F'.
- Screwed on Bonnet, Rising Stem.
- Provision for re-packing under pressure.
- Renewable 13% Cr. Stainless Steel (AISI 410) working parts.
- Handwheel Operated.

Also available with PTFE Seating for Air and Gas applications, at a nominal extra price.

Suitable For

Steam	■
Water	■
Oil	■
Air	■
Gases	■


Test Pressure (Hydraulic) Shell : 35 kg/cm²g (500 psig) Working Pressure (Steam) 10.55 kg/cm²g (150 psig)
Maximum Working Temperature 225°C

Materials of Construction

Name of Part	Material	Specification
Body, Bonnet & Gland	Bronze	IS 318 Gr. LTB 2
Disc Nut & Gland Nut	Bronze	IS 318 Gr. LTB 2
Stem, Disc & Body Seat Ring	Stainless Steel	AISI 410
Handwheel	Cast Iron	IS 210 Gr. FG 200
Nut & Washer	Carbon Steel	IS 1367
Gland Packing	Asbestos	IS 4687

Sizes / Dimensions

Inches	mm	A	B	C
1/2	15	82	117	70
3/4	20	96	132	80
1	25	112	148	86
1 1/4	32	119	176	102
1 1/2	40	132	188	102
2	50	157	216	127
2 1/2	65	185	248	150
3	80	213	270	170
4	100	248	332	190



Zoloto Industries
Zoloto House, 11th Milestone, Lambra, Nakodar Road,
Jalandhar - 144 026
Punjab, India

Phones : +91 181 4676666 (100 Lines)
Facsimile : +91 181 2792500 & 2251600
Email : zoloto@vsnl.com & sales@zolotovalves.com
Web : http://www.zolotovalves.com