



Salient Features

- Screwed Female Ends to IS 554 / BS 21 / ISO 7.
- Push Button Type, Spring Loaded.
- Full Flow, Smooth in Operation.
- Heavy Pattern.
- No chance of spring losing its tension or catching rust.

Can also be supplied with Chrome Plating, at a nominal extra price.

Suitable For

Steam
Water
Oil
Air
Gases


Test Pressure (Hydraulic) Shell : 24 kg/cm²g (340 psig) Seat : 16 kg/cm²g (225 psig)

Materials of Construction

Name of Part	Material	Specification
Body & Gland	Bronze	IS 318 Gr. LTB 2
Stem cum Disc	Bronze	IS 318 Gr. LTB 2
Push Cap	Bronze	IS 318 Gr. LTB 2
Bottom Cap	Bronze	IS 318 Gr. LTB 2
Screw	Bronze	BS 2874 / 2872
Gland Packing	PTFE	BS EN 12086-1
Spring	Stainless Steel	AISI 304

Sizes / Dimensions

Inches	mm	A	B
1/2	15	60	79
3/4	20	70	82
1	25	78	90



Zoloto Industries
Zoloto House, 11th Milestone, Lambra, Nakodar Road,
Jalandhar - 144 026
Punjab, India

Phones : +91 181 4676666 (100 Lines)
Facsimile : +91 181 2792500 & 2251600
Email : zoloto@vsnl.com & sales@zolotovalves.com
Web : http://www.zolotovalves.com