



Salient Features

- Screwed Female Ends to IS 554 / BS 21 / ISO 7.
- Tapered Plug accurately ground to ensure water tightness.
- Quarter Turn, Rectangular Port.
- High Quality lubricated Gland Packing.

Suitable For

Steam
Water
Oil
Air
Gases

Test Pressure (Hydraulic) Shell : 10.55 kg/cm²g (150 psig) Seat : 7 kg/cm²g (100 psig)

Materials of Construction

Name of Part	Material	Specification
Body	Bronze	IS 318 Gr. LTB 2
Plug	Bronze	IS 318 Gr. LTB 2
Gland	Bronze	IS 318 Gr. LTB 2
Gland Packing	Graphited Asbestos	IS 4687
Bolt	Carbon Steel	IS 1367

Sizes / Dimensions

Inches	mm	A	B
1/2	15	55	60
3/4	20	67	70
1	25	75	78
1 1/4	32	90	94
1 1/2	40	100	102
2	50	123	117



Zoloto Industries
Zoloto House, 11th Milestone, Lambra, Nakodar Road,
Jalandhar - 144 026
Punjab, India

Phones : +91 181 4676666 (100 Lines)
Facsimile : +91 181 2792500 & 2251600
Email : zoloto@vsnl.com & sales@zolotovalves.com
Web : http://www.zolotovalves.com