



**Salient Features**

- Screwed Female Ends to IS 554 / BS 21 / ISO 7.
- Screwed in Bonnet, Suitable for both Horizontal and Vertical Lines.
- Permits flow in one direction and shuts automatically if the flow reverses.
- Disc is guided in Body and Bonnet.
- Chrome Plated Body and Bonnet.

**Suitable For**

Steam
Water
Oil
Air
Gases


Test Pressure (Hydraulic) Shell : 20 kg/cm<sup>2</sup>g (285 psig) Seat : 13.50 kg/cm<sup>2</sup>g (192 psig)

**Materials of Construction**

Name of Part	Material	Specification
Body	Forged Brass	IS 6912 Gr. FLB
Bonnet	Forged Brass	IS 6912 Gr. FLB
Disc	PVC	IS 15225
Rubber Washer	Nitrile Rubber	IS 5192-1
Spring	Stainless Steel	AISI 304

**Sizes / Dimensions**

Inches	mm	A	B
1/2	15	55	1/2"
3/4	20	61	3/4"
1	25	67	1"



Zoloto Industries  
Zoloto House, 11th Milestone, Lambra, Nakodar Road,  
Jalandhar - 144 026  
Punjab, India

Phones : +91 181 4676666 (100 Lines)  
Facsimile : +91 181 2792500 & 2251600  
Email : zoloto@vsnl.com & sales@zolotovalves.com  
Web : http://www.zolotovalves.com