



Salient Features

- Screwed Male End to BSP.
- Gland Packed.
- Available for both, Right Hand and Left Hand.
- Polished Body.

Glass Tube is not provided with this product.

Suitable For

Steam
Water
Oil
Air
Gases


Test Pressure (Hydraulic) 21.10 kg/cm²g (300 psig) Working Pressure (Steam) 10.55 kg/cm²g (150 psig)
Maximum Working Temperature 225°C

Materials of Construction

Name of Part	Material	Specification
Arms & Plug	Bronze	IBR 282 (a) (iv) Gr.B
Gland & Gland Nut	Bronze	IBR 282 (a) (iv) Gr.B
Union Nut & Lock Nut	Bronze	IBR 282 (a) (iv) Gr.B
Bottom Nut	Bronze	IBR 282 (a) (iv) Gr.B
Gasket	Steam Jointing Sheet	IS 2712 Gr. W/3
Glass Tube	Toughened Glass	BS 3463
Gland Packing	Graphited Asbestos	IS 4687

Sizes / Dimensions

Inches	mm	A
1/2	15	102
3/4	20	125



Zoloto Industries
Zoloto House, 11th Milestone, Lambra, Nakodar Road,
Jalandhar - 144 026
Punjab, India

Phones : +91 181 4676666 (100 Lines)
Facsimile : +91 181 2792500 & 2251600
Email : zoloto@vsnl.com & sales@zolotovalves.com
Web : <http://www.zolotovalves.com>