



Salient Features

- Screwed Female Ends to IS 554 / BS 21 / ISO 7.
- Single Piece Design.
- Meant for Vertical Lines Only.
- Permits flow in one direction and closes automatically if the flow reverses.
- Design Standard IS 778, Class-1.
- Can be provided with Rubber 'O' Ring Seating also, at no extra cost.

Suitable For

- Steam
- Water
- Oil
- Air
- Gases


Test Pressure (Hydraulic) Shell : 1.5 MPa Seat : 0.25 MPa

Materials of Construction

Name of Part	Material	Specification
Body	Bronze	IS 318 Gr. LTB 2
Disc	Bronze	IS 318 Gr. LTB 2
Nut	Brass	IS 319 Gr. 2 (Half Hard)
Split Pin	Phosphorus Bronze	IS 7608
'O' Ring	Nitrile Rubber	IS 5192-1

Sizes / Dimensions

Inches	mm	A
1/2	15	65
3/4	20	70
1	25	75
1 1/4	32	85
1 1/2	40	95
2	50	110



Zoloto Industries
Zoloto House, 11th Milestone, Lambra, Nakodar Road,
Jalandhar - 144 026
Punjab, India

Phones : +91 181 4676666 (100 Lines)
Facsimile : +91 181 2792500 & 2251600
Email : zoloto@vsnl.com & sales@zolotovalves.com
Web : <http://www.zolotovalves.com>