



Salient Features

- Screwed Female Ends to BSPT.
- Stainless Steel (AISI 304) / Brass (IS 410) 1 mm diameter hole perforated sheet screen is guided in body and bonnet.
- Fine finish and smooth contours to minimize pressure drop inside the strainer.
- Large screening area makes the strainer highly efficient in performance.

Suitable For

| |
|-------|
| Steam |
| Water |
| Oil |
| Air |
| Gases |


Test Pressure (Hydraulic) 21.10 kg/cm²g (300 psig) Working Pressure (Steam) 10.55 kg/cm²g (150 psig)
Maximum Working Temperature 220°C

Materials of Construction

| Name of Part | Material | Specification |
|---------------|----------------------|-------------------|
| Body & Bonnet | Cast Iron | IBR 86-93 Gr. A |
| Screen | S.S / Brass | AISI 304 / IS 410 |
| Gasket | Steam Jointing Sheet | IS 2712 Gr. W/3 |

Sizes / Dimensions

| Inches | mm | A | B |
|--------|----|-----|-----|
| 1/2 | 15 | 76 | 71 |
| 3/4 | 20 | 98 | 85 |
| 1 | 25 | 133 | 95 |
| 1 1/4 | 32 | 155 | 110 |
| 1 1/2 | 40 | 178 | 116 |
| 2 | 50 | 222 | 140 |



Zoloto Industries
Zoloto House, 11th Milestone, Lambra, Nakodar Road,
Jalandhar - 144 026
Punjab, India

Phones : +91 181 4676666 (100 Lines)
Facsimile : +91 181 2792500 & 2251600
Email : zoloto@vsnl.com & sales@zolotovalves.com
Web : http://www.zolotovalves.com