



Salient Features

- Flanged Ends to DIN 2545 ND 40.
- Bolted Cover, Straight Pattern.
- Renewable 13% Cr. Stainless Steel (AISI 410) working parts.
- Minimum pressure drop inside the body due to well contoured body design.

Suitable for thermic fluid application also.

Suitable For

- Steam
- Water
- Oil
- Air
- Gases


Test Pressure (Hydraulic) Shell : 60 bar Maximum Working Pressure : 40 bar

Materials of Construction

Name of Part	Material	Specification
Body, Cover & Disc	Cast Steel	IBR 73-80 Gr.B
Body Seat Ring & Disc Ring	Stainless Steel	AISI 410
Stud	Alloy Steel	ASTM A193 Gr.B7
Nut	H.T. Steel	ASTM A194 Gr.2H
Gasket	Spiral wound S.S (AISI 304), Graphite Filled	BS 3381

Sizes / Dimensions

Inches	mm	A	B
1/2	15	130	86
3/4	20	150	86
1	25	160	100
1 1/4	32	180	102
1 1/2	40	200	113
2	50	230	123
2 1/2	65	290	155
3	80	310	170
4	100	350	192
5	125	400	220
6	150	480	250
8	200	600	275



Zoloto Industries
Zoloto House, 11th Milestone, Lambra, Nakodar Road,
Jalandhar - 144 026
Punjab, India

Phones : +91 181 4676666 (100 Lines)
Facsimile : +91 181 2792500 & 2251600
Email : zoloto@vsnl.com & sales@zolotovalves.com
Web : http://www.zolotovalves.com



JAYARAJ PIPE TRADERS

48/425 Q, JAYARAJ HOUSE, ELAMAKKARA, COCHIN 682 026
TEL. No. 0484 253 0785, 240 8008, 240 8009. FAX: 0484 253 0785
E-mail: jaypipescochin@gmail.com, sales@jayarajpipes.com
Web: www.jayarajpipes.com

