



**Salient Features**

- Screwed Female Ends to IS 554 / BS 21 / ISO 7.
- Quarter Turn, Rectangular Port.
- Tapered Plug accurately ground to ensure water tightness.
- Smooth in Operation.

**Suitable For**

Steam
Water
Oil
Air
Gases


Test Pressure (Hydraulic) Shell : 10.55 kg/cm<sup>2</sup>g (150 psig) Seat : 7 kg/cm<sup>2</sup>g (100 psig)

**Materials of Construction**

Name of Part	Material	Specification
Body	Bronze	IS 318 Gr. LTB 2
Plug	Bronze	IS 318 Gr. LTB 2
Washer	Bronze	IS 318 Gr. LTB 2
Nut	Brass	IS 319 Gr. 2 (Half Hard)

**Sizes / Dimensions**

Inches	mm	A	B
1/2	15	55	75
3/4	20	67	87
1	25	75	97
1 1/4	32	90	120
1 1/2	40	100	138
2	50	123	170



Zoloto Industries  
Zoloto House, 11th Milestone, Lambra, Nakodar Road,  
Jalandhar - 144 026  
Punjab, India

Phones : +91 181 4676666 (100 Lines)  
Facsimile : +91 181 2792500 & 2251600  
Email : zoloto@vsnl.com & sales@zolotovalves.com  
Web : <http://www.zolotovalves.com>