



Salient Features

- Screwed Male End to IS 554 / BS 21 / ISO 7.
- Tapered Plug accurately ground for water tightness and is retained by a nut at the bottom.
- Provided with an Integral Locking Device.
- Polished Body.

Can also be supplied with Chrome Plating, at a nominal extra price.

Suitable For

Steam
Water
Oil
Air
Gases


Test Pressure (Hydraulic) Shell : 10.55 kg/cm²g (150 psig) Seat : 7 kg/cm²g (100 psig)

Materials of Construction

Name of Part	Material	Specification
Body	Bronze	IS 318 Gr. LTB 2
Plug	Bronze	IS 318 Gr. LTB 2
Washer	Bronze	IS 318 Gr. LTB 2
Nut	Brass	IS 319 Gr. 2 (Half Hard)
Spring Washer	Spring Steel	IS 4072

Sizes / Dimensions

Inches	mm	A
1/2	15	65
3/4	20	70



Zoloto Industries
Zoloto House, 11th Milestone, Lambra, Nakodar Road,
Jalandhar - 144 026
Punjab, India

Phones : +91 181 4676666 (100 Lines)
Facsimile : +91 181 2792500 & 2251600
Email : zoloto@vsnl.com & sales@zolotovalves.com
Web : <http://www.zolotovalves.com>