



Salient Features

- Flanged Ends to BS 10 Table 'J'.
- Stainless Steel (AISI 304) perforated 1 mm diameter hole sheet screen is guided in body and cover.
- Drain Plug to remove the accumulated foreign particles.
- Fine finish and smooth contours to minimize pressure drop inside the strainer.
- Large screening area makes the strainer more efficient.

Suitable for thermic fluid application also.

Suitable For

- Steam
- Water
- Oil
- Air
- Gases


Test Pressure (Hydraulic) 49 kg/cm²g (700 psig) Maximum Working Pressure (Steam) 24.60 kg/cm²g (350 psig)
Maximum Working Temperature 425°C

Materials of Construction

Name of Part	Material	Specification
Body & Cover	Cast Steel	IBR 73-80 Gr.B
Plug	Carbon Steel	IS 1367
Screen	Stainless Steel	AISI 304
Gasket	Steam Jointing Sheet	IS 2712 Gr. W/3
Stud	Alloy Steel	ASTM A193 Gr.B7
Nut	H.T. Steel	ASTM A194 Gr.2H

Sizes / Dimensions

Inches	mm	A	B
1	25	181	135
1 1/2	40	260	200
2	50	276	225
2 1/2	65	286	250
3	80	296	280
4	100	403	312
6	150	476	364



Zoloto Industries
Zoloto House, 11th Milestone, Lambra, Nakodar Road,
Jalandhar - 144 026
Punjab, India

Phones : +91 181 4676666 (100 Lines)
Facsimile : +91 181 2792500 & 2251600
Email : zoloto@vsnl.com & sales@zolotovalves.com
Web : http://www.zolotovalves.com



JAYARAJ PIPE TRADERS

48/425 Q, JAYARAJ HOUSE, ELAMAKKARA, COCHIN 682 026
TEL. No. 0484 253 0785, 240 8008, 240 8009. FAX: 0484 253 0785
E-mail: jaypipescochin@gmail.com, sales@jayarajpipes.com
Web: www.jayarajpipes.com

