



Salient Features

- Flanged Ends to DIN 2533 PN 16RF upto 150 mm.
- Angle Pattern, Bolted Cover.
- Renewable 13% Cr. Stainless Steel (AISI 410) working parts.
- Minimum pressure drop inside the body due to streamlined body design.

Pressure and Temperature for 200 mm Valve is as per PN10 and flanges to PN 10RF.

Suitable For

Steam
Water
Oil
Air
Gases


Test Pressure (Hydraulic) 26 kg/cm²g (370 psig) Working Pressure (Steam) 13 kg/cm²g (185 psig)
Maximum Working Temperature 220°C

Materials of Construction

Name of Part	Material	Specification
Body, Cover & Disc	Cast Iron	IBR 86-93 Gr. A
Stud & Nut	Carbon Steel	IS 1367
Disc Ring & Body Seat Ring	Stainless Steel	AISI 410
Gasket	Steam Jointing Sheet	IS 2712 Gr. W/3

Sizes / Dimensions

Inches	mm	A	B
1/2	15	90	52
3/4	20	95	54
1	25	100	57
1 1/4	32	105	64
1 1/2	40	115	76
2	50	125	83
2 1/2	65	145	95
3	80	155	108
4	100	175	125
6	150	225	182
8	200	275	190



Zoloto Industries
Zoloto House, 11th Milestone, Lambra, Nakodar Road,
Jalandhar - 144 026
Punjab, India

Phones : +91 181 4676666 (100 Lines)
Facsimile : +91 181 2792500 & 2251600
Email : zoloto@vsnl.com & sales@zolotovalves.com
Web : http://www.zolotovalves.com



JAYARAJ PIPE TRADERS

48/425 Q, JAYARAJ HOUSE, ELAMAKKARA, COCHIN 682 026
TEL. No. 0484 253 0785, 240 8008, 240 8009. FAX: 0484 253 0785
E-mail: jaypipescochin@gmail.com, sales@jayarajpipes.com
Web: www.jayarajpipes.com

