



Salient Features

- Screwed Male End to IS 554 / BS 21 / ISO 7.
- Tapered Plug accurately ground for air tightness which is retained by a nut at the bottom.
- Operating Handle is an integral part of the Plug.
- Polished Body.

Suitable For

Steam
Water ■
Oil
Air ■
Gases


Test Pressure (Hydraulic) Shell : 10.55 kg/cm²g (150 psig) Seat : 7 kg/cm²g (100 psig)

Materials of Construction

Name of Part	Material	Specification
Body	Bronze	IS 318 Gr. LTB 2
Plug	Bronze	IS 318 Gr. LTB 2
Hose	Bronze	IS 318 Gr. LTB 2
Nut	Brass	IS 319 Gr. 2 (Half Hard)
Washer	Bronze	IS 318 Gr. LTB 2

Sizes / Dimensions

Inches	mm	A
1/4	8	40
3/8	10	45
1/2	15	50



Zoloto Industries
Zoloto House, 11th Milestone, Lambra, Nakodar Road,
Jalandhar - 144 026
Punjab, India

Phones : +91 181 4676666 (100 Lines)
Facsimile : +91 181 2792500 & 2251600
Email : zoloto@vsnl.com & sales@zolotovalves.com
Web : <http://www.zolotovalves.com>